

TECHNICAL DATA SHEET

Textile Backlit Fabric (FAB PEARL)

Description

Fabric : 130 GSM
 Coating : Polyurethane (PU)
 Width : 1.32m / 1.60m / 2.54m / 3.20m
 Length : 50 Mtrs



Item	Unit	Value	Testes Method
Fabric	100% PES (150D)		DIN EN ISO2060
Total Weight	130	g / sqm	DIN53352 BS3424 method 5A
Weight of Fabric	95	g / sqm	DIN53352 BS3424 method 5B
Weight of PU Coating	35	g / sqm	DIN53352 BS3424 method 5B
Tensile Strength	Warp : 750 Weft : 650	N /5cm	DIN53354 BS3424 method 6A
Tearing Strength	Warp : 45 Weft : 40	N	DIN53356 BS3424 method 7A
Adhesion	20	N /5cm	DIN53357 BS3425 method 9B
Suitable Temperature	-20 ----- +70	C	DIN53372 BS3424 method 10
Flame Retardancy	B1 / FR		

Lacquering

Declaration: Please choose VAGUS products suitably according to relative provisions or industrial standards. VAGUS bears the responsibility for the specified technical and performance data on this page only. VAGUS is not responsible for any other liability. (The technical data on this page is calculated on average, and $\pm 5\%$ tolerance is acceptable)