

TECHNICAL DATA SHEET

FG LAM

Description

- Product : Anti-Slip Anti-Friction Clear Floor Lamination Film
- Film : 100 micron (including adhesive) White (Gloss), Monomeric Calendered PVC film
- Adhesive : Permanent Clear Solvent based Acrylic adhesive
- Release liner : One Side PE and Silicon Coated Kraft Paper, 140gsm
- Width : 1.27
- Length : 50mtrs
- Shelf : Up to 1 Year at 23 C and relative humidity of 50%
- Durability : Up to 1 Year



Item	Unit	Value	Testes Method
Thickness- Film	μm	150	GB/T6672-2001
Thickness- Finished Product	μm	285	GB/T6672-2001
Adhesive Weight	g/m	35-40	FINAT12
Elongation at Break MD	%	90-100	GB/T1040.1-2006
Elongation at Break CD	%	90-100	GB/T1040.1-2006
Dimesnsional Stability MD	%	≤0.1	FINAT14
Dimesnsional Stability CD	%	≤0.1	FINAT14
Initial Adhesion	N/25mm	R10	FINAT9
180 Peel -20 Minutes	N/25mm	9-11	FINAT9
180 Peel -24 Hours	N/25mm	12-14	FINAT1

Applied Printers : Not For Printing

Applied Printers: Inkjet printing with Solvent / ECO Solvent based inks, UVorLatex inks

Declaration: Please choose VAGUS products suitably according to relative provisions or industrial standards. VAGUS bears the responsibility for the specified technical and performance data on this page only. VAGUS is not responsible for any other liability. (The technical data on this page is calculated on average, and ±5% tolerance is acceptable)