

BA-TW-CP-827.865-24 -G5

BackLED TW CP G5 | LED modules for light advertising and backlighting



Product family features

- Light color: dynamic 2700...6500 K
- Compatible with OSRAM OPTOTRONIC constant voltage drivers / dimmers
- Color consistency in 3 SDCM
- Patented Square Lens technology
- IP66 rating
- Lifetime (L70/B50): 50,000 h (temperature at $T_c = 75\text{ °C}$)

Product family benefits

- Backside injection technology for high protection level
- 5 year guarantee

Areas of application

- Daylight simulation
- Channel letters
- Luminous areas and ceilings



Product datasheet

Technical data

Electrical data

Nominal voltage	24.0 V
Accidental reverse input voltage protection up to	24 V
Input voltage range	23.4...24.9 V
Type of current	DC



Photometrical data

Light color LED	White
Luminous efficacy	127/150 lm/W

LED module information

Number of LEDs per module	4
Number of LED modules per chain	30
Minimum operable number of LED modules	1

Dimensions & weight



Product weight	925.00 g
Length	77.9 mm
Width	17.8 mm
Height	12.4 mm

Temperatures & operating conditions

Temperature range in operation at Tc point	-25...75 °C
Temperature range at storage	-25...85 °C

Additional product data

Product datasheet

Product remark	Modules perfectly matched to OSRAM OPTOTRONIC LED drivers (see relevant table)/For current photometric data and important safety, installation and application information (see www.osram.com/led-systems)./In view of the complex manufacturing process for light emitting diodes, the typical values given above for the technical LED parameters are merely statistical values that do not necessarily correspond to the actual technical parameters of an individual product; individual products may vary from the typical values
ID of contained light source [GMS]	LS_SHZ_600837
Predecessor EAN	4052899452954

Capabilities

Dimmable	Yes
Dimming range	1...100 %

Certificates & standards

Energy consumption	60 kWh/1000h
Type of protection	IP66
Standards	CE/ENEC/UL/BIS
Approval marks – approval	CE / ENEC
Energy efficiency class of the contained light source	E

Logistical data

Commodity code	853951000000
-----------------------	--------------

Environmental information








Information according Art. 33 of EU Regulation (EC) 1907/2006 (REACH)	
Date of Declaration	23-05-2022
Primary Article Identifier	4052899627253
Candidate List Substance 1	No declarable substances contained
Declaration No. in SCIP database	No declarable substances contained

Additional product information

- Installation of LED modules (with power supplies) needs to be made under consideration of all valid regulations and norms.
- Installation by qualified electrician only.
- Please see the relevant application guides and instructions sheets for more detailed safety and mounting information. Additional information is available on request.

Product datasheet

Download Data

File	
	User instruction BackLED XL CP G5 TW UI
	Product Datasheet Product datasheet BA TW CP 827.865 24V G5
	Brochures Technical application guide BackLED and BoxLED portfolio (EN)
	Certificates ENEC of BackLED CP G5
	Certificates UL certificate of Compliance BackLED CP G5
	CAD data 3-dim 3D drawing of BackLED CP 24V G5 TW
	IES data IES file of BA TW CP 827.865 24 G5

Logistical Data

Product code	Product description	Packaging unit (Pieces/Unit)	Dimensions (length x width x height)	Volume	Gross weight
4052899627253	BA-TW-CP-827.865-24 - G5	Shipping carton box 10	355 mm x 255 mm x 240 mm	21.73 dm ³	9900.00 g

The mentioned product code describes the smallest quantity unit which can be ordered. One shipping unit can contain one or more single products. When placing an order, for the quantity please enter single or multiples of a shipping unit.

Accessories Optional

Product description	Accessory name	Accessory code
BA-TW-CP-827.865-24 -G5	BA -MP-L-G5-2M	▶ 4052899629189
BA-TW-CP-827.865-24 -G5	BA -MP-SM-G5-2M	▶ 4052899629196
BA-TW-CP-827.865-24 -G5	BA -CLIP-SM-G5	▶ 4052899629349

Disclaimer

Subject to change without notice. Errors and omission excepted. Always make sure to use the most recent release.